



Color Diffused Typ

Holder Color: Black

**Absolute Maximum Rating (Ta=25°C)**

Item	Symbol	Value	Unit
DC Forward Current	IF	30	mA
Pulse Forward Current*	IFP	100	mA
Reverse Voltage	VR	5	V
Power Dissipation	PD	78	mW
Operating Temperature	Topr	-30~ +85	°C
Storage Temperature	Tstg	-40 ~ +100	°C
Lead Soldering Temperature	Tsol	260°C /5sec	-

\*Pulse width Max 10ms Duty ratio max 1/10

**Electrical –Optical Characteristics (Ta=25°C)**

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
DC Forward Voltage	VF	IF=20mA	1.8	2.1	2.6	V
DC Reverse Current	IR	VR=5V	-	-	10	µA
Domi. Wavelength	λD	IF=20mA	585	590	595	nm
Luminous Intensity	IV	IF=20mA	110	120	-	mcd
50% Power Angle	2θ1/2	IF=20mA	-	30	-	deg

\*1 Tolerance of measurements of dominant wavelength is +1nm

\*2 Tolerance of measurements of luminous intensity is +15%

\*3 Tolerance of measurements of forward voltage is  $\pm 0.1$ V